



CL012N English

CL012N Dry Autoclave with timer

Choose **CYAN CL012N** and get the following advantages:

- Low electricity consumption
- Very stable temperature
- Excellent thermal isolation
- Easy to clean
- Easy to program
- Visual alarm indicator
- Adjustable shelf height
- Programmable autoclaving time
- Timer only starts when the set temperature is reached

Technical Data:

- Working range: ambient + 5 °C up to 200 °C
- Precision of temperature control: +/- 0,5 °C at 100°C
+/- 1,0 °C at 200°C
- Capacity: 50 liters
- Natural convection
- PID temperature control
- Overheating protection
- Double-wall fiberglass insulation
- Stainless steel interior
- Double glass window
- Chamber dimensions: 38 x 36,5 x 39 cm (W x D x H)
- Overall dimensions: 48 x 47,5 x 69,5 cm (W x D x H)
- Weight: 32 kg
- Power: 1000 W
- Power supply: 110 V – 60 Hz (CL012-110)
or 220 V – 50/60 Hz (CL012-220)

Accessories included:

- 2 vertically adjustable shelves

Order code:

- CL012N-110: **Dry Autoclave with timer** (110 V- 60 Hz)
- CL012N-220: **Dry Autoclave with timer** (220 V – 50/60 Hz)

Dry Autoclave with Timer



Contact: e-mail: cypress@diagnostics.be
tel: + 32 (0)15 67 67 68

Headquarters: Cypress Diagnostics
Langdorpsesteenweg 160
3201 Langdorp
Belgium

Factory: Nijverheidsstraat 8
2235 Hulshout
Belgium

URL: www.diagnostics.be

Your Distributor

Dry Autoclave EN 2018-01

