



CL011 English

CL011 Incubator

Choose **CYAN CL011** and get the following advantages:

- Low electricity consumption
- Very stable temperature
- Excellent thermal isolation
- Easy to clean
- Easy to program
- Visual alarm indicator
- Adjustable shelf height

Accessories included:

- 2 vertically adjustable shelves

Technical Data:

- Working range: ambient + 5 °C up to 70 °C
- Precision of temperature control: +/- 0,3 °C at 37 °C
+/- 0,4 °C at 70 °C
- Capacity: 30 liters
- Natural convection
- PID temperature control
- Double doors (samples visible through an acrylic door)
- Overheating protection
- Double wall
- Fiberglass insulation
- Stainless steel interior
- Chamber dimensions: 32,5 x 31 x 31,5 cm (W x D x H)
- Overall dimensions: 42,5 x 42 x 61 cm (W x D x H)
- Weight: 23 kg
- Power: 300 W
- Power supply: 110 V – 60 Hz (CL011-110)
or 220 V – 50/60 Hz (CL011-220)

Order code:

- CL011-110: **Incubator** (110 V – 60 Hz)
- CL011-220: **Incubator** (220 V – 50/60 Hz)



Incubator



Your Distributor

Contact: e-mail: cypress@diagnostics.be
tel: + 32 (0)15 67 67 68

Headquarters: Cypress Diagnostics
Langdorpsesteenweg 160
3201 Langdorp
Belgium

Factory: Nijverheidsstraat 8
2235 Hulshout
Belgium

URL: www.diagnostics.be